



Dim "A"	Dim "B"	Dim "C"	Dim "D"	Dim "E"	Dim "F"
4.03"	3.77"	4.27"	4.41"	.91"	
4.03"	7.64"	4.27"	8.28"	1.32"	
6.03"	5.71"	6.27"	6.35"	1.13"	.44"
6.03"	11.61"	6.27"	12.25"	1.76"	
8.08"	7.70"	8.32"	8.34"	1.34"	.69"
12.11"	11.61"	12.35"	12.25"	1.76"	
11.0"	8.14"	11.24"	8.78"	1.36"	
18.03"	11.61"	18.27"	12.25"	1.76"	
24.03"	17.35"	24.27"	17.99"	2.36"	
36.03"	23.18"	36.27"	23.82"	2.99"	

MATERIAL LIST

- ① — LENS - Option 1: 1/16" laser cut non glare clear PETG. Option 2: 1/16" laser cut clear photopolymer tactile panel.
- ② — FRAME - Extruded aluminum frame rail, surface painted with acrylic polyurethane, color per Architects specification.
- ③ — ENDCAPS - Option 1: 1/8" laser cut acrylic, clear, black or painted per Architects specification. Option 2: 1/8" laser cut black haircell ABS, unfinished or painted per Architects specification. Option 3: 1/8" router cut aluminum painted per Architects specification.
- ④ — CAP SCREWS - 1/2", 6-32 Stainless steel button head cap screw.
- ⑤ — BACK PANEL - .080" aluminum back applied with 1/32" foam adhesive.
- ⑥ — INSERT - .020" polystyrene, polycarbonate or laminate insert.

The contents of this drawing is confidential and proprietary of SilverLeaf Design, LLC dba Kroy Sign Systems and any reproduction or disclosure of it without the written consent of Kroy Sign Systems is strictly prohibited.



DRAWN BY STEPHEN E. HATCLIFF	
CHECKED BY	
DATE 10/01/12	PART NO. CVXXXX
SHEET 1 of 1	REVISION 0

COMMENTS

ADA Signs - Curved
Changeable Message