



MATERIAL LIST

- ① — 1"(o.d) square steel tubing finished with acrylic polyurethane.
- ② — Fabricated expanded PVC panel finished with acrylic polyurethane.
- ③ — Black polyethylene injection molded plastic endcap.
- ④ — 1/4"-20 x 2" black alloy steel button head hex socket cap screw.
- ⑤ — 1/2" black SBR rubber stem bumper.
- ⑥ — LENS - 1/16" laser cut non glare clear acrylic with 3/8" subsurface painted border and polished edges. Color: black, grey, beige, brown, architectural grey or painted per Architects specification.
- ⑦ — SPACER - .060" X .25" neoprene.

Dim "A"	Dim "B"	Dim "C"	Dim "D"	Dim "E"
48.0"	12.0"	18.0"	20.0"	12.0"
60.0"	12.0"	24.0"	26.0"	18.0"
60.0"	18.0"	24.0"	26.0"	18.0"
72.0"	18.0"	36.0"	38.0"	24.0"
Custom	Custom	Custom	Custom	Custom

The contents of this drawing is confidential and proprietary of SilverLeaf Design, LLC dba Kroy Sign Systems and any reproduction or disclosure of it without the written consent of Kroy Sign Systems is strictly prohibited.



DRAWN BY STEPHEN E. HATCLIFF	
CHECKED BY	
DATE 10/01/12	PART NO. SUXXXCU
SHEET 1 of 1	REVISION 0

COMMENTS
Sign Stands Changeable Message